KERN FFN3K0.5IPN



Compact organ balance, protected against water splashes through stainless steel construction and IP65 rating, also with EC type approval [M]



Mager	irina	system
IVIEASU	a ii u	37310111

measuring system		
Adjustment options:	External calibration	
Eccentric loading at 1/3 [Max]:	2,500 g	
Linearity:	1 g	
Number of weighing ranges:	1	
Readability [d]:	500 mg	
Recommended adjusting weight:	3 kg (M3)	
Repeatability:	500 mg	
Resolution:	6000	
Stabilisation time under laboratory conditions:	2 s	
Tare range:	-3 kg	
Warm up time:	30 min	
Weighing capacity [Max]:	3 kg	
Weighing system:	Strain gauge	
Weighing units:	kg lb	

Display

Display digit height (large):

2,500 cm

Environmental conditions

Maximum humidity:	95 %
·····,	
Maximum operating temperature:	40 °C
maximum oporating tomporation	
Minimum ambient temperature:	-10 °C
•	
Minimum humidity:	25 %

Power supply					
Battery:	no battery				
Charging time:	12 h				
Input voltage:	110 V - 230 V AC				
Mains adapter:	Mains adapter external				
Mains adapter/adapter included:	US UK EURO CH				
Operating time (Backlight off):	50 h				
Operating time (Backlight on):	30 h				
Services (optional)					
Adjustment at the location of installation: 961-247					
DAkkS Certificate:	963-127				
Category					
Brand:	KERN				
Category:	Balances				
Product Group:	Bench scale				
	Denen Searc				
Packaging & shipping					
Delivery:	24 h				
Dimensions packaging (WxDxH):	380 x 403 x 206 mm				
Gross weight:	4,600 kg				
Net weight:	3,850 kg				
Shipping method:	Parcel service				
UN number:	2800				
Construction					
Dimensions housing (WxDxH):	243 x 300 x 127 mm				
Level indicator:	yes				
Material weighing plate:	stainless steel				
Overall dimensions mounted (WxDxH):	243 x 300 x 127 mm				
Revolving screw feet:	yes				
Weighing surface (WxD):	233 x 193 mm				

Piktogramme

STANDARD

	2	666	EED	B		
CAL EXT	UNIT	IP 65	ACCU	MULTI	DMS	1 DAY

OPTION



FACTORY

