## KERN EW4200-2NM

The classic balance with robust tuning fork measuring system





Measuring system					
Measuring system					
Adjustment options:	External calibration				
Linearity:	20 mg				
Minimum weight (USP):	20 g				
Readability [d]:	10 mg				
Recommended adjusting weight:	2 kg (E2); 2 kg (E2)				
Repeatability:	10 mg				
Resolution:	420000				
Stabilisation time under laboratory conditions:	2 s				
Warm up time:	4 h				
Weighing capacity [Max]:	4,200 kg				
Weighing units:	ct dwt g lb mo oz ozt tl (HK) tl (Singap. Malays) tl (Tw) tol				
Display					
Display digit height:	1,700 cm				
Technical data about verification					
Verification class:	II				
Counting					
Counting resolution:	420000				
Mininum piece weight at piece	10 mg				

counting (Laboratory:

counting (Normal):

Mininum piece weight at piece

Functions				
Counting function:	yes			
Percentage determination:	yes			
Weighing with tolerance range:	yes			
Environmental conditions				
Maximum humidity:	80 %			
Maximum operating temperature:	30 °C			
Minimum ambient temperature:	10 °C			
Power supply				
Charging time:	12 h			
Input voltage:	220 V - 240 V AC 50 Hz			
Mains adapter:	Mains adapter external			
Mains adapter/adapter included:	CHEURO			
Operating time (Backlight off):	32 h			
Operating time (Backlight on):	12 h			
Rechargeable battery:	Rchrg. battery optional			
Service				
DAkkS Certificate:	963-127			
Category				
Brand:	KERN			
Category:	Balances			
Product Group:	Precision balance			
Packaging & shipping				
Delivery:	24 h			
Dimensions packaging (WxDxH):	320 x 410 x 230 mm			
Gross weight:	4,040 kg			
Net weight:	2,862 kg			
Shipping method:	Parcel service			
Construction				
Casing material:	Plastic			
Dimensions housing (WxDxH):	192 x 265 x 87 mm			
Level indicator:	yes			
Material weighing plate:	stainless steel			
Revolving screw feet:	yes			
Weighing surface (WxD):	180 x 160 mm			

100 mg

## KERN EW4200-2NM

The classic balance with robust tuning fork measuring system



## Piktogramme

## STANDARD

CAL INT  CAL EXT	• 6000.1 RS 232	GLP PRINTER	PCS	% Percent	UNIT	-√+ ⊙ Э୬ TOL	UNDER
OPTION							
ACCU MULTI	DAkks +3 days						

FACTORY

